


YM-2301HAR



Feature

- 150.0 (L) x 79.0 (W) x 40.3 (H) mm
- N+1 Redundant
- Support PMBus 1.1
- High Power Density 11.87 W/in³
- Application for IPC/Storage/Embedded server/Networking



INPUT	
Input Voltage	90-264VAC
Input Frequency	47-63Hz
Input Current	5.0A max at 115VAC, 2.5A max at 240VAC
Inrush Current	60A max at 264VAC
Power Factor	0.98 at 115VAC / 60Hz, 0.93 at 230VAC / 50Hz
Earth Leakage Current	1.75mA max at 240VAC / 50Hz

GENERAL	
Efficiency	80 Plus SILVER certified, Highest efficiency 89% at 230VAC
Power Density	10.29 W/in ³
MTBF	100 kHrs per Bellcore SR-332 at 25°C ambient

ENVIRONMENTAL	
Operating Temperature	0 to 50°C
Operating Humidity	5 - 90%, Non-condensing
Storage Temperature	-40°C to +70 °C
Operating Altitude	Sea level to 5,000 M
Shock Operating	5G, 11mSec, half sine 3 axes
Non-Operating	30G, 11mSec, half sine 3 axes
Vibration Operating	0.5G at 10Hz to 500Hz, 3 axes
Non-Operating	2G at 10Hz to 300Hz, 3 axes

EMC & SAFETY	
Emissions	EN55022, class B Conducted / EN55022, class B Radiated
Harmonic Currents	EN61000-3-2
Voltage Flicker	EN61000-3-3
EFT/Burst	EN61000-4-4
Surge	EN61000-4-5
Conducted Immunity	EN61000-4-6
Safety Approvals	UL/cUL, TUV, CB, CE, CCC, FCC

Output	Minimum Load	Maximum Load	Condition	Ripple & Noise
+12V	0.5A	24A		120mV p-p
+5Vsb	0.1A	4.0A		75mV p-p

YM-2301HAR

