


YM-2851FAR



Feature

- 300.0 (L) x 50.5 (W) x 40.0 (H) mm
- N+1 Redundant
- Support PMBus 1.2
- Application for IPC/Storage/Embedded server/Networking



INPUT	
Input Voltage	90-264VAC, 190-310VDC
Input Frequency	47-63Hz
Input Current	12.0A / 115VAC, 6.0A / 230VAC
Inrush Current	60A max at 264VAC
Power Factor	0.98/115VAC, 0.96/230VAC
Earth Leakage Current	1.5mA max for each power supply at 264VAC

GENERAL	
Efficiency	80 Plus PLATINUM certified, Highest efficiency 94% at 230VAC
Power Density	
MTBF	100 kHrs per Bellcore SR-332 at 25°C ambient

ENVIRONMENTAL	
Operating Temperature	0 to 50°C
Operating Humidity	20%~90%, Non-condensing
Storage Temperature	-40°C to +80 °C
Operating Altitude	Sea level to 5,000 M
Shock Operating	10G, no malfunction
Non-Operating	50G no damage
Vibration Operating	0.01G ² /Hz at 10Hz, 0.02G ² /Hz at 20Hz
Non-Operating	0.02G ² /Hz form 20Hz to 1kHz

EMC & SAFETY	
Emissions	EN55032, class B
Harmonic Currents	EN61000-3-2
Voltage Flicker	EN61000-3-3
EFT/Burst	EN61000-4-4
Surge	EN61000-4-5
Conducted Immunity	EN61000-4-6
Safety Approvals	UL/cUL, TUV, CB, CE, CCC, FCC

Output	Minimum Load	Maximum Load	Condition	Ripple & Noise
+12V	1A	70A		120mV p-p
+5Vsb	0.1A	3.0A		50mV p-p

YM-2851FAR

