

Technical drawing of the 1000 Series 1U Rack Mountable Power Supply Unit, showing front, top, and side views with dimensions in millimeters (mm) and inches (in).

Front View Dimensions:

- Overall Width: 50.5 ± 0.3 mm [1.988 ± 0.014 in]
- Overall Height: 40.0 ± 0.35 mm [1.575 ± 0.014 in]
- Mounting Hole Spacing (Top): 150.0 ± 0.5 mm [5.906 ± 0.020 in]
- Mounting Hole Spacing (Bottom): 159.0 ± 0.5 mm [6.26 ± 0.020 in]
- Input Connector Spacing: 26.0 ± 0.3 mm [1.024 ± 0.012 in]
- Output Connector Spacing: 8.0 ± 0.3 mm [0.315 ± 0.012 in]
- Output Connector Offset: 0.1 mm
- Label Area: SPEC LABEL
- Mounting Hole Diameter: $\varnothing 4.5$ mm
- Input Connector: 2-C1.5X45°
- Output Connector: 2-C1.5X45°

Top View Dimensions:

- Overall Width: 50.5 ± 0.3 mm [1.988 ± 0.014 in]
- Overall Height: 40.0 ± 0.35 mm [1.575 ± 0.014 in]
- Mounting Hole Spacing (Top): 150.0 ± 0.5 mm [5.906 ± 0.020 in]
- Mounting Hole Spacing (Bottom): 159.0 ± 0.5 mm [6.26 ± 0.020 in]
- Input Connector Spacing: 26.0 ± 0.3 mm [1.024 ± 0.012 in]
- Output Connector Spacing: 8.0 ± 0.3 mm [0.315 ± 0.012 in]
- Output Connector Offset: 0.1 mm
- Label Area: SPEC LABEL
- Mounting Hole Diameter: $\varnothing 4.5$ mm
- Input Connector: 2-C1.5X45°
- Output Connector: 2-C1.5X45°

Side View Dimensions:

- Overall Width: 50.5 ± 0.3 mm [1.988 ± 0.014 in]
- Overall Height: 40.0 ± 0.35 mm [1.575 ± 0.014 in]
- Mounting Hole Spacing (Top): 150.0 ± 0.5 mm [5.906 ± 0.020 in]
- Mounting Hole Spacing (Bottom): 159.0 ± 0.5 mm [6.26 ± 0.020 in]
- Input Connector Spacing: 26.0 ± 0.3 mm [1.024 ± 0.012 in]
- Output Connector Spacing: 8.0 ± 0.3 mm [0.315 ± 0.012 in]
- Output Connector Offset: 0.1 mm
- Label Area: SPEC LABEL
- Mounting Hole Diameter: $\varnothing 4.5$ mm
- Input Connector: 2-C1.5X45°
- Output Connector: 2-C1.5X45°